

FX HIDRO WATER-BASED FOGGING CARRIER

FX HIDRO Water-Based Carrier is a carrier product and additive to prepare water soluble (Emulsifiable Concentration) water-suspendable and water-flowable pesticides of all kinds for fogging application.

PHYSICAL QUALITIES

FX Hidro Water-Based Fogging Carrier is a mixture of alcohols and water. It is a limpid liquid of higher viscosity as water and neutral (PH=7). Flash point about 130°C. FX Hidro is quickly absorbed by the air after application because of its unlimited water solubility.

BIOLOGICAL BEHAVIOUR

Overdose of FX Hidro has no phytotoxic influence as long as applying machines are used which avoid overheating and guarantee droplet sized between 1 and 30 microns.

However, fogging recommendations should be carefully observed. Never fog directly at plants or any objects because of force, temperature and high concentration of active material.

FX Hidro Water-Based Fogging Carrier does not effect the efficiency of the dissolved and suspended pesticides.

APPLICATION :

1. Make sure fogging machines is operating correctly.
2. Determine the amount of pesticides recommended for per hectare.
3. Mix the calculated pesticides with the calculated amount of water.
4. Now add the amount of FX Hidro according to required fog density.
Stir continuously and transfer to the solution tank using a funnel with strainer.
5. After fogging, clean nozzle, solution tank, conduits, fog tap. Refer to maintenance procedure.

Fog Density	FX Hidro	Water
High / Thick	3 Liter	1 Liter
Average / Standard	2 Liter	2 Liter
Light / Thin	1 Liter	3 Liter



SAFETY, QUALITY AND STOCKING

FX Hidro Water-Based Fogging Carrier must be stocked with inaccessibility to children and unauthorized persons. Despite the fact that contact with skin is less problematic, skin contact should be avoided. Do not ingest, consumption may cause serious problem. LD50 (rat) 6,000 mg/kg.

FX Hidro Water-Based Fogging Carrier should be stored in original container at cool temperature. FX Hidro Water-Based Carrier does not effect normal plastic materials and can be stocked in polyamide and polythene tanks if needed.

GUARANTEE

The manufacturer guarantees only that FX Hidro Water-Based Fogging Carrier a dilutant for wettable and soluble water for use with fogging applicators and is true to label claims.

No claim are made for effectiveness. In no case will the manufacturer be liable for damages due to incorrect stocking, faulty application, non-observance of safety standards, or non-observance of pesticide label direction.

10 Liter & 25 Liter



SYARIKAT PERNIAGAAN KEMUNCAK_(000640840-P)

No. 43, Jalan Meranti Jaya 12, Meranti Jaya Industrial Park,
47120 Puchong, Selangor Darul Ehsan.

Tel : 03-8060 8346
Fax : 03-8060 1180

Office h/p : 012-369 4346
Email : kemuncak@myjaring.net